




## LED HIGH MAST LIGHT 200W 240W







DIMENSIONS




77.6

**L**ength: 14.25 in (362 mm)


Height: 13.46 in (342 mm)


▼ Width: 5.2 in (132 mm)







20°

















OPTICAL SPECS	LSHM-200W-LV(XXK)	LSHM-240W-LV(XXK)
Efficency:	Up to 160 Lm/W±3%	Up to 155 Lm/W±3%
Lumen:	32,000 Lumens	37,800 Lumens
Color Temp:	3000K / 4000K / 5000K / 5700K	
Light Source:	Lumileds 5050	
Beam Angle:	20° / 40° / 60° / 90° 140*100°/Milky PC 120°	

#### ▶ ELECTRICAL SPECS

Wattage:	200 Watt	240 Watt
Input Voltage:	100-277VAC	
Power Frequency:	50/60 Hz	
Driver:	Meanwell ELG-240-48A	
Dimming:	Dimmable / Non-dimmable	

#### **▶** OTHER DETAILS

Fixture Material:	Marine grade aluminum
IP Rating:	IP65 (TUV report available)
Module rotatable:	Module rotatable up & down 15°
Lifespan:	>50,000 Hours
Dimensions:	13.46 x 14.25 x 5.2 in (342 x 362 x 132mm)
Certficates:	TUV ,CE ,SAA ,CB, LM79, LM80, ISTMT, LCP



















# **LED HIGH MAST LIGHT**



### **APPLICATION**

- ►Outdoor lighting ► Security lighting ► Industrial lighting
- ► Sports field lighting ► Construction site lighting
- ► Highmast lighting



### **▼ADJUSTABLE** MOUNT



Round installation plate

