

# LED Bollard Light TL811A/B






patented




SPECIFICATION	TL811A	TL811B
Input Power (W)	25W	25W/ 35W
Beam Angle	150°	
CRI	≥70	
Color Temp.	3000K/4000K/5000K/5700K	
Voltage	100-277V	
Power Factor	0.95	
Housing	Extruded Aluminum	
Working Temp.	-40 C~+50 C	
IP grade	IP66	
IK	IK08	
LED Life Span (L70/B50)	>60000 hours	
Reference Qty/20FT(pcs)	537	537
Reference Qty/40HQ(pcs)	1279	1279

\* DLC pending



TL811A 150°



TL811B 150°

### Application:

- parks
- squares
- pedestrian street
- residential areas



# LED Bollard Light TL811C/D






patented




SPECIFICATION	TL811C	TL811D
Input Power (W)	25W	25W/ 35W
Beam Angle	150°	
CRI	≥70	
Color Temp.	3000K/4000K/5000K/5700K	
Voltage	100-277V	
Power Factor	0.95	
Housing	Extruded Aluminum	
Working Temp.	-40 C~+50 C	
IP grade	IP66	
IK	IK08	
LED Life Span (L70/B50)	>60000 hours	
Reference Qty/20FT(pcs)	537	537
Reference Qty/40HQ(pcs)	1279	1279

\* DLC pending



TL811C 150°



TL811D 150°

### Application:

- parks
- squares
- pedestrian street
- residential areas

